

Proceeding Paper

# Optimizing MAG Welding Input Variables to Maximize Penetration Depth Using Particle Swarm Optimization Algorithm <sup>†</sup>

Mohamed Mezaache <sup>1,\*</sup>, Omar Fethi Benaouda <sup>1</sup>, Saad Chaouch <sup>1</sup>, Badreddine Babes <sup>2</sup> and Rachid Amraoui <sup>1</sup>

<sup>1</sup> Research Center in Industrial Technologies CRTI, P.O. Box 64, Cheraga 16014, Algeria; o.benaouda@crti.dz (O.F.B.); s.chaouch@crti.dz (S.C.); r.amraoui@crti.dz (R.A.)

<sup>2</sup> Thin Films Development and Applications Unit UDCMA-CRTI, Industrial Zone 15 A, Setif 19000, Algeria; b.babes@crti.dz

\* Correspondence: mohamedmezaache@gmail.com

<sup>†</sup> Presented at the 1st International Conference on Computational Engineering and Intelligent Systems, Online, 10–12 December 2021.

**Abstract:** Systems based on artificial intelligence, such as particle swarm optimization and genetic algorithm have received increased attention in many research areas. One of the main objectives in the gas metal arc welding (GMAW) process is to achieve maximum depth of penetration (DP) as a characteristic of quality and stiffness. This article has examined the application of particle swarm optimization algorithm to obtain a better DP in a GMAW and compare the results obtained with the technique of genetic algorithms. The effect of four main welding variables in GMAW process which are the welding voltage, the welding speed, the wire feed speed and the nozzle-to-plate distance on the DP have been studied. For the implementation of optimization, a source code has been developed in MATLAB 8.3. The results showed that, in order to obtain the upper penetration depth, it is necessary that: the welding voltage, the welding speed and the nozzle-to-plate distance must be at their lowest levels; the wire feed speed at its highest level.

**Keywords:** artificial intelligence; particle swarm optimization; genetic algorithm; GMAW; penetration depth; optimization; MATLAB



**Citation:** Mezaache, M.; Benaouda, O.F.; Chaouch, S.; Babes, B.; Amraoui, R. Optimizing MAG Welding Input Variables to Maximize Penetration Depth Using Particle Swarm Optimization Algorithm. *Eng. Proc.* **2022**, *14*, 5. <https://doi.org/10.3390/engproc2022014005>

Academic Editors: Abdelmadjid Recioui, Hamid Bentarzi and Fatma Zohra Dekhandji

Published: 25 January 2022

**Publisher's Note:** MDPI stays neutral with regard to jurisdictional claims in published maps and institutional affiliations.



**Copyright:** © 2022 by the authors. Licensee MDPI, Basel, Switzerland. This article is an open access article distributed under the terms and conditions of the Creative Commons Attribution (CC BY) license (<https://creativecommons.org/licenses/by/4.0/>).